



Pipe-Ray Ipari Kft. 1111 Budapest Lágymányosi utca 12, Fsz. 2. ajtó

Tax no.: 27775677-2-07, HU 27775677

<https://piperayipari.hu/>

## SPARK Base 16W30

### Product description:

Water-dispersion base for the production of varnish products used in the manufacture of matt carton packaging.

### Physical characteristics:

Solid content:	26±2%
pH measurement:	8,3 ± 0,2
Viscosity (20°C):	40 ± 5 (DIN-4)

### Product features:

- The final product is used in the paint and varnish industry in the manufacture in the matt carton packaging.

## GENERAL GUIDELINE

### Application viscosity:

As supplied. The viscosity is strongly depending on temperature.

For specific environmental/food compliance requirements, please contact our technicians for more information.

### Ecology and safety:

The recommended storage temperature is 18 – 22 C. Shelf life is 12 months in closed original packaging. Avoid direct sunlight.

### Storage:

Avoid any contacts with skin and eyes. All works should be proceeded in the ventilated working area. For more information, please, see the MSDS.

### Safe handling:

## STIR COATING WELL BEFORE USE!

### Notes:

- All information provided in this Technical Data Sheet (TDS) including the recommendations for application is based on our current knowledge and experiences.
- This document is provided for informational purposes only and do not release users from carrying out their own tests and trials.
- We reserve the right to change product properties according to the newest requirements of technical progress, amendments and additions to the list of restricted raw materials. These changes do not bring negative impact on the technical characteristics of the product.

### Prior tests are recommended before any commercial work.

The information contained herein is based on our knowledge, true and correct. Any recommendations are made without guarantee, as the conditions of use are beyond our control. Our technical department may be contacted for further information.